



PNEUMATIC ACTUATOR HP-SERIES



CE 0036 PED EAC  

Valve automation leader HKC

HCAG-HP-16 Rev.0



Contents

Introduction	1
Specification	1
Features	2
Rack & Pinion Design	3
Scotch Yoke Design	5
Performance Data	7
Dimensional Drawing	9
Air Consumption	12
Weight	12
Declutchable Gear Override - HGO-Series	13
Dimension - Pinion Shaft Star Adapter	14

Introduction

HP-series pneumatic actuators are specifically designed to respond to your demanding needs on the valve automation market. It provides a wide range of torque outputs to suit quarter turn ball, butterfly, plug valves and dampers for complete valve automation solutions. The latest manufacturing technologies have been used to ensure high quality and long life-cycle of the HP-series. Moreover, our extensive inventory & engineering capabilities allow us to provide reliable and safe product to our customer with satisfaction.



Specification

- Rack & pinion design (HP-035 - HP-210) / Scotch yoke design (HP-211, 212)
- Single acting or double acting
- Wide range of torque outputs
- Pressure range
 - Max. operating pressure: 8 bar
- Temperature range
 - Standard: -20 to +80 °C
 - Option: -35 to +80 °C (low)
 - 20 to +150 °C (high)
- Travel angle
 - Standard: 90° travel angle with ±5° adjustable travel stops (standard)
 - Option: Other travel angles (60°, etc.) with travel adjustment (option)
- Lubrication: All moving parts are lubricated at the factory for long-life cycle of the actuator
- Mounting standard
 - Top/side: VDI/VDE 3845 NAMUR standard
 - Bottom: ISO 5211 standard

Features

■ Body

Extruded aluminum alloy body is anodized inside/outside for corrosion resistance and to reduce friction with the pistons for a long life cycle.

■ Indicator

A disc open / close indicator is standard on all models.

■ Travel Stops

External $\pm 5^\circ$ adjustable travel stops in both open and close positions.

■ End Caps

Aluminum die-casting end caps are chromate coated and then polyester powder coated to maximize resistance against potentially corrosive elements.

■ Spring

High tensile spring sets are consisted of high strength alloy steel to provide high performance in fail safe and emergency shut down operations.

■ Pinion Shaft

Alloy steel pinion is electroless nickel plated in order to reduce friction, to provide maximum wear resistance and to protect against corrosion under severe conditions.

■ Piston Guides

Self-lubricating (polypropylene + GF) piston guides provide high reliability and stability.

■ Piston Seals

NBR rubber pinion seals provide trouble free operation at standard temperature ranges. Optional viton seals are available for higher temperature range and silicon seals are available for lower temperature range.


■ Piston

Die-casted aluminum dual pistons are fitted with high quality piston seals and guides, providing high ratio of output torque to input air pressure. All HP-series actuators are designed to provide constant output torque




Rack & Pinion Design


Torque diagram (HP-035 - HP-210)




Double acting



Single acting




Double acting operation



Counterclockwise


1. Apply an air pressure to port A.
2. Then as the pistons move apart, the drive shaft turns counterclockwise.
3. Air volume exhausts through port B.



Clockwise


1. Apply an air pressure to port B.
2. Then as the pistons move inwards, the drive shaft turns clockwise.
3. Air volume exhausts through port A.

Single acting operation



Counterclockwise

1. Apply an air pressure to port A.
2. Then as the pistons move apart, the springs are compressed and the drive shaft turns counterclockwise.
3. Air volume exhausts through port B.




Clockwise (on air failure)

1. In the event of an air failure
2. As the compressed springs push the pistons inwards, the drive shaft turns clockwise.
3. Air volume exhausts through port A and comes in through port B..

Note: If air fail to counterclockwise is required, the pistons must be inverted.


■ Bill of Materials




Part No.	Unit Q'ty	Part Description	Material	Corrosion Protection	Optional Material
1	2	Position indicator	Polypropylene + GF	-	-
2	1	Position indicator holder	Polypropylene + GF	-	-
3	1	Spring clip (pinion)	Stainless steel	Nickel plated (HP-160, HP-200)	-
4	1	Thrust washer (pinion)	Stainless steel	-	-
5	1	Thrust bearing (pinion)	Polyphthalamide	-	-
6	1	Body	Extruded aluminium alloy	Anodized / hard-anodized	-
7	2	Bearing (piston back)	Polyphthalamide	-	-
8	2	Piston	Die cast aluminium	Anodized / hard-anodized	-
9	2	O-ring (piston)	Nitrile (NBR70)	-	FKM, VMQ
10	2	Bearing (piston head)	Polyphthalamide	-	-
11	8	Cover bolt washer	Stainless steel	-	-
12	2	Cover bolt (end cover)	Stainless steel	-	-
13	2	Right and left end cover	Die cast aluminium	Chromate + polyester coated	-
14	2	O-ring (end cover)	Nitrile (NBR70)	-	FKM, VMQ
15	2	Piston guide	Polyphthalamide	-	-
16	1	O-ring (pinion top)	Nitrile (NBR70)	-	FKM, VMQ
17	1	Bearing (piston top)	Nylon 46	-	-
18	1	Thrust bearing (pinion)	Polyphthalamide	-	-
19	1	Open, close cam (stop arrangement)	Stainless steel	-	-
20	1	Drive shaft	Steel alloy	Nickel plated	-
21	1	Bearing (piston bottom)	Nylon 46	-	-
22	1	O-ring (pinion bottom)	Nitrile (NBR70)	-	FKM, VMQ
23	1	O-ring (stop screw)	Nitrile (NBR70)	-	FKM, VMQ
24	2	Stop bolt washer	Stainless steel	-	-
25	2	Stop nut	Stainless steel	-	-
26	2	Stop bolt	Stainless steel	-	-
27	5 - 12	Spring	High alloy spring steel	Epoxy coated	-
28	1	Spring holder	Polypropylene + GF	-	-

Scotch Yoke Design


Torque diagram (HP-211 - HP-212)




Double acting



Single acting




Double acting operation



Counterclockwise


1. Apply an air pressure to port A.
2. Then as the pistons move apart, the drive shaft turns counterclockwise.
3. Air volume exhausts through port B.



Clockwise


1. Apply an air pressure to port B.
2. Then as the pistons move inwards, the drive shaft turns clockwise.
3. Air volume exhausts through port A.

Single acting operation



Counterclockwise

1. Apply an air pressure to port A.
2. Then as the pistons move apart, the springs are compressed and the drive shaft turns counterclockwise.
3. Air volume exhausts through port B.




Clockwise (on air failure)

1. In the event of an air failure
2. As the compressed springs push the pistons inwards, the drive shaft turns clockwise.
3. Air volume exhausts through port A and comes in through port B.

Note: If air fail to counterclockwise is required, the pistons must be inverted.

■ Bill of Materials



Part No.	Unit Q'ty	Part Description	Material
1	1	Cylinder body	Aluminum alloy
2	1	Drive shaft	Steel alloy
3	1	Yoke pin	Steel
4	1	Yoke	Steel
5	1	Bottom spacer	Nylon
6	1	Stem bottom bearing	Stainless steel
7	1	Stem bottom O-ring	NBR
8	2	Piston	Aluminum
9	2	Snap ring	Stainless steel
10	1	Roller pin	Steel
11	1	Shaft	Steel
12	2	Snap ring	Stainless steel
13	3	Piston back bearing	PTFE
14	2	Hole sealant	NBR
15	1	Top spacer	Nylon
16	1	OCT cam	Steel
17	1	Stem thrust bearing	Stainless steel
18	1	Stem top bearing	Stainless steel
19	1	Stem top O-ring	NBR
20	1	Teflon washer	PTFE
21	1	Stem thrust washer	Stainless steel

Part No.	Unit Q'ty	Part Description	Material
22	5	Snap ring	Stainless Steel
23	1	Indicator	ABS
24	1	Indicator holder cover	ABS
25	2	Double acting cover	Aluminum
26	2	Piston O-ring	NBR
27	3	Piston head bearing	PTFE
28	2	Cover O-ring	NBR
29	2	Stop bolt O-ring	NBR
30	2	Stop bolt washer	Stainless steel
31	2	Stop bolt nut	Stainless steel
32	2	Stop bolt	Stainless steel
33	1 - 2	Inner spring	Spring steel
34	1 - 2	Outer spring	Spring steel
35	1 - 2	Spring bolt	Stainless steel
36	1 - 2	Spring retainer	Aluminum
37	1 - 2	Spring O-ring	NBR
38	1 - 2	Spring washer	Steel
39	1 - 2	Spring nut	Stainless steel
40	2	Spring retainer cover	Aluminum
41	8	Cover bolt	Stainless steel

Performance Data (Rack & Pinion)

Double Acting (Torque: Nm)

Model	AIR SUPPLY									
	2.5 bar	3 bar	3.5 bar	4 bar	4.5 bar	5 bar	5.6 bar	6 bar	7 bar	8 bar
HP-035	3.8	4.5	5.3	6	6.8	7.5	8.3	9	10.5	12
HP-050	8.3	10	11.7	13.3	15	16.6	18.3	20	23.3	26.6
HP-063	15	17.9	20.9	23.9	26.9	29.9	32.9	35.9	41.9	47
HP-066	20.9	25.1	29.3	33.5	37.7	41.9	46.1	50.3	58.6	67
HP-075	28.7	34.5	40.2	45.9	51.7	57.4	63.2	68.9	80.4	92
HP-088	46.1	55.3	64.5	73.7	83	92.2	101.4	110.6	129	147
HP-100	68.2	81.9	95.5	109.2	122.8	136.5	150.1	163.8	191.1	214
HP-115	107.5	129	150.5	172	193.5	215	236.5	258	301	344
HP-125	138.5	166.2	194	221.7	249.4	277.1	304.8	332.5	387.9	443.3
HP-145	217.5	261	304.5	348	391.5	435	478.5	522	609	696
HP-160	283.7	340.5	397.2	454	510.7	567.4	624.2	680.9	794.4	908
HP-180	382.8	459.4	536	612.5	689.1	765.7	842.2	918.8	1071.9	1225
HP-200	531.7	638	744.4	850.7	957.1	1063.4	1169.8	1276.1	1488.8	1701.5
HP-210	586.9	704.3	821.6	939	1056.4	1173.8	1291.2	1408.5	1643.3	1878.1

Single Acting (Torque: Nm)

Model	Actuator Spring	2.5 bar		3 bar		3.5 bar		4 bar		4.5 bar		5 bar		5.6 bar		6 bar		7 bar		8 bar		Spring		
		0	90	0	90	0	90	0	90	0	90	0	90	0	90	0	90	0	90	0	90	0	90	0
HP 050S	S 05	4.9	3.4	6.6	5.1	8.3	6.8	9.9	8.4	11.6	10.1	13.2	11.7	14.9	13.4							4.9	3.4	
	S 06	4.3	2.5	6	4.2	7.7	5.9	9.3	7.5	11	9.2	12.6	10.8	14.3	12.5	16	14.2					5.8	4	
	S 07	3.6	1.5	5.3	3.2	7	4.9	8.6	6.5	10.3	8.2	11.9	9.8	13.6	11.5	15.3	13.2	18.6	16.5			6.8	4.7	
	S 08			4.6	2.2	6.3	3.9	7.9	5.5	9.6	7.2	11.2	8.8	12.9	10.5	14.6	12.2	17.9	15.5			7.8	5.4	
	S 09					5.6	2.9	7.2	4.5	8.9	6.2	10.5	7.8	12.2	9.5	13.9	11.2	17.2	14.5	20.5	17.8	8.8	6.1	
	S 10							6.6	3.6	8.3	5.3	9.9	6.9	11.6	8.6	13.3	10.3	16.6	13.6	19.9	16.9	9.7	6.7	
	S 11									7.6	4.3	9.2	5.9	10.9	7.6	12.6	9.3	15.9	12.6	19.2	15.9	10.7	7.4	
	S 12														10.2	6.6	11.9	8.3	15.2	11.6	18.5	14.9	11.7	8.1
	D.ATORQUE		8.3		10		11.7		13.3		15		16.6		18.3		20		23.3		26.6		8.4	5.5
	HP 063S	S 05	9.5	6.6	12.4	9.5	15.4	12.5	18.4	15.5	21.4	18.5	24.4	21.5	27.4	24.5							10.1	6.7
S 06		8.3	4.9	11.2	7.8	14.2	10.8	17.2	13.8	20.2	16.8	23.2	19.8	26.2	22.8	29.2	25.8					11.8	7.8	
S 07		7.2	3.2	10.1	6.1	13.1	9.1	16.1	12.1	19.1	15.1	22.1	18.1	25.1	21.1	28.1	24.1	34.1	30.1			13.5	8.9	
S 08				9	4.4	12	7.4	15	10.4	18	13.4	21	16.4	24	19.4	27	22.4	33	28.4			15.2	10	
S 09						10.9	5.7	13.9	8.7	16.9	11.7	19.9	14.7	22.9	17.7	25.9	20.7	31.9	26.7	37	31.8	16.9	11.1	
S 10								12.8	7	15.8	10	18.8	13	21.8	16	24.8	19	30.8	25	35.9	30.1	16.9	11.1	
S 11											14.7	8.3	17.7	11.3	20.7	14.3	23.7	17.3	29.7	23.3	34.8	28.4	18.6	12.2
S 12															19.6	12.7	22.6	15.7	28.6	21.7	33.7	26.8	20.2	13.3
D.ATORQUE			15		17.9		20.9		23.9		26.9		29.9		32.9		35.9		41.9		47		12	7.6
HP 066S		S 05	13.3	8.9	17.5	13.1	21.7	17.3	25.9	21.5	30.1	25.7	34.3	29.9	38.5	34.1							14.4	9.1
	S 06	11.8	6.5	16	10.7	20.2	14.9	24.4	19.1	28.6	23.3	32.8	27.5	37	31.7	41.2	35.9					16.8	10.6	
	S 07			14.5	8.3	18.7	12.5	22.9	16.7	27.1	20.9	31.3	25.1	35.5	29.3	39.7	33.5	48	41.8			19.2	12.1	
	S 08			13	5.9	17.2	10.1	21.4	14.3	25.6	18.5	29.8	22.7	34	26.9	38.2	31.1	46.5	39.4			21.6	13.7	
	S 09					15.6	7.7	19.8	11.9	24	16.1	38.2	20.3	32.4	24.5	36.6	28.7	44.9	37	53.3	45.4	21.6	13.7	
	S 10							18.3	9.5	22.5	13.7	26.7	17.9	30.9	22.1	35.1	26.3	43.4	34.6	51.8	43	24	15.2	
	S 11									21	11.3	25.2	15.5	29.4	19.7	33.6	23.9	41.9	32.2	50.3	40.6	26.4	16.7	
	S 12														27.9	17.3	32.1	21.5	40.4	29.8	48.8	38.2	28.8	18.2
	D.ATORQUE		20.9		25.1		29.3		33.5		37.7		41.9		46.1		50.3		58.6		67		17.3	11.1
	HP 075S	S 05	17.6	11.4	23.4	17.2	29.1	22.9	34.8	28.6	40.6	34.4	46.3	40.1	52.1	45.9							20.8	13.3
S 06		15.4	7.9	21.2	13.7	26.9	19.4	32.6	25.1	38.4	30.9	44.1	36.6	49.9	42.4	55.6	48.1					24.2	15.5	
S 07		13.2	4.5	19	10.3	24.7	16	30.4	21.7	36.2	27.5	41.9	33.2	47.7	39	53.4	44.7	64.9	56.2			27.7	17.7	
S 08				16.8	6.8	22.5	12.5	28.2	18.2	34	24	39.7	29.7	45.5	35.5	51.2	41.2	62.7	52.7			31.2	19.9	
S 09						20.3	9	26	14.7	31.8	20.5	37.5	26.2	43.3	32	49	37.7	60.5	49.2	72.1	60.8	31.2	19.9	
S 10								23.8	11.3	29.6	17.1	35.3	22.8	41.1	28.6	46.8	34.3	58.3	45.8	69.9	57.4	34.6	22.1	
S 11										27.4	13.6	33.1	19.3	38.9	25.1	44.6	30.8	56.1	42.3	67.7	53.9	38.1	24.3	
S 12															36.7	21.7	42.4	27.4	53.9	38.9	65.5	50.5	41.5	26.5
D.ATORQUE			28.7		34.5		40.2		45.9		51.7		57.4		63.2		68.9		80.4		92		28.9	18.3
HP 088S		S 05	27.8	17.2	37	26.4	46.2	35.6	55.4	44.8	64.7	54.1	73.9	63.3	83.1	72.5							34.7	22
	S 06	24.1	11.4	33.3	20.6	42.5	29.8	51.7	39	61	48.3	70.2	57.5	79.4	66.7	88.6	75.9					40.4	25.7	
	S 07	20.4	5.7	29.6	14.9	38.8	24.1	48	33.3	57.3	42.6	66.5	51.8	75.7	61	84.9	70.2	103.3	88.6			46.2	29.3	
	S 08			26	9.1	35.2	18.3	44.4	27.5	53.7	36.8	62.9	46	72.1	55.2	81.3	64.4	99.7	82.8			52	33	
	S 09					31.5	12.5	40.7	21.7	50	31	59.2	40.2	68.4	49.4	77.6	58.6	96	77	114	95	52	33	
	S 10							37	15.9	46.3	25.2	55.5	34.4	64.7	43.6	73.9	52.8	92.3	71.2	110.3	89.2	57.8	36.7	
	S 11									42.7	19.5	51.9	28.7	61.1	37.9	70.3	47.1	88.7	65.5	106.7	83.5	63.5	40.3	
	S 12														57.4	32.1	66.6	41.3	85	59.7	103	77.7	69.3	44
D.ATORQUE		46.1		55.3		64.5		73.7		83		92.2		101.4		110.6		129		147		34.7	22	

Performance Data (Scotch Yoke)

Double Acting (Torque: Nm)


HP-211	Start	Run	End	HP-212	Start	Run	End
4.2 bar	1,507	753	1,312	4.2 Bar	3,011	1,506	2,622
5.6 bar	2,009	1,005	1,750	5.6 Bar	4,017	2,006	3,498
7 bar	2,511	1,255	2,187	7 Bar	5,022	2,509	4,373

Single Acting (Torque: Nm)

HP-211S	AIR TORQUE			SPRING TORQUE		
	Start	Run	End	Start	Run	End
4.2 bar	1,114	452	634	678	283	393
5.6 bar	1,385	537	724	1,026	446	624

HP-212S	AIR TORQUE			SPRING TORQUE		
	Start	Run	End	Start	Run	End
4.2 bar	2,226	904	1,266	1,356	565	780
5.6 bar	2,769	1,074	1,446	2,045	883	1,243


Dimensional Drawing (HP-035)



Unit: mm

Model	Flange L (ISO 5211)		A	B	C	D	E	F	G	H	I	K	O	S	T	U	V	W	X
	Q	R																	
HP-035	F03/F05	M5/M6	126	54	30	24	69	49	25	50	PF	1/8"	20	4	4	12	24	16	32
	Ø36/Ø50	10/9																	

■ HP-050 - HP-210




Unit: mm

Model	Flange L (ISO 5211)		R																
	Q	M/N(min)	A	B	C	D	E	F	G	H	I	K	O	S	T	U	V	W	X
HP-050	F03/F05 Ø36/Ø50	M5/M6 14/11	144	72	42	30	93	73	30	80	PF	1/8"	20	4	4	12	24	16	32
HP-063	F05/F07 Ø50/Ø70	M6/M8 18/14	163	85	47	38	107	87	30	80	PF	1/8"	20	4	4	12	24	16	32
HP-066	F05/F07 Ø50/Ø70	M6/M8 18/14	202	85	47	38	107	87	30	80	PF	1/8"	20	4	4	12	24	16	32
HP-075	F05/F07 Ø50/Ø70	M6/M8 22/17	210	96	53.5	42.5	124	104	30	80	PF	1/8"	20	4	4	12	24	16	32
HP-088	F05/F07/F10 Ø50/Ø70/Ø102	M6/M8/M10 22/17	247	108	58.5	49.5	136	116	30	80	PF	1/8"	20	4	4	12	24	16	32
HP-100	F05/F07/F10 Ø50/Ø70/Ø102	M6/M8/M10 22/17	268	123	67	56	148	128	30	80	PF	1/4"	20	4	4	12	24	16	32
HP-115	F07/F10 Ø70/Ø102	M8/M10 32/22	316	141	77	64	166	146	30	80	PF	1/4"	20	4	4	12	24	16	32
HP-125	F07/F10/F12 Ø70/Ø102/Ø125	M8/M10/M12 32/22	347	151	82	69	179	159	30	80	PF	1/4"	20	4	4	12	24	16	32
HP-145	F10/F12 Ø102/Ø125	M10/M12 36/27	414	172	92	80	209	179	30	130	PF	1/4"	30	4	4	12	24	16	32
HP-160	F10/F12 Ø102/Ø125	M10/M12 36/27	467	190	101	89	226	196	30	130	PF	1/4"	30	4	4	12	24	16	32
HP-180	F10/F12 Ø102/Ø125	M10/M12 39/36	497	206	107	99	251	221	30	130	PF	1/4"	30	4	4	12	24	16	32
HP-200	F14 Ø140	M16 39/36	555	227	116	111	277	247	30	130	PF	1/4"	30	4	4	12	24	16	32
HP-210	F14 Ø140	M16 43/36	628	236	120	116	286	256	30	130	PF	1/4"	30	4	4	12	24	16	32

Dimensional Drawing

HP-211 / 212



Unit: mm

Model	Flange L (ISO 5211)		R	B	C	D	E	F	G	H	I	K	O	S	T	U	V	W	X
	Q	M/N(min)																	
HP-211	F16	M20	236	120	116	286	256	30	130	PF	1/4"	30	4	4	12	24	16	32	
	Ø165	54/46																	
HP-212	F16	M20	236	120	116	286	256	30	130	PF	1/4"	30	4	4	12	24	16	32	
	Ø165	54/46																	

Air Consumption

■ Double Acting

Unit: liter (ℓ)

Model	Volume	2.5 bar	3 bar	3.5 bar	4 bar	4.5 bar	5 bar	5.6 bar	6 bar	7 bar	8 bar
HP-035	0.2	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.6	1.8
HP-050	0.3	1.1	1.2	1.4	1.5	1.7	1.8	2.0	2.1	2.5	2.8
HP-063	0.5	1.8	2.0	2.3	2.6	2.8	3.1	3.3	3.6	4.1	4.6
HP-066	0.5	2.1	2.5	2.8	3.1	3.4	3.7	4.0	4.3	4.9	5.5
HP-075	0.8	2.9	3.3	3.7	4.1	4.5	4.9	5.3	5.7	6.5	7.4
HP-088	1.3	4.7	5.3	6.0	6.6	7.3	8.0	8.6	9.3	10.6	11.9
HP-100	1.8	6.4	7.4	8.3	9.2	10.1	11.0	12.0	12.9	14.7	16.5
HP-115	3.0	10.7	12.3	13.8	15.3	16.9	18.4	19.9	21.5	24.5	27.6
HP-125	3.8	13.6	15.6	17.5	19.4	21.4	23.3	25.2	27.2	31.0	34.9
HP-145	6.2	22.2	25.4	28.5	31.7	34.9	38.0	41.2	44.3	50.7	57.0
HP-160	7.3	26.2	29.9	33.6	37.3	41.0	44.8	48.5	52.2	59.6	67.1
HP-180	11.2	40.1	45.8	51.5	57.3	63.0	68.7	74.4	80.1	91.5	102.9
HP-200	15.4	55.2	63.0	70.9	78.7	86.6	94.4	102.3	110.1	125.8	141.5
HP-210	16.0	57.3	65.5	73.6	81.8	89.9	98.1	106.3	114.4	130.7	147.1
HP-211	13.7	49.1	56.1	63.0	70.0	77.0	84.0	91.0	98.0	111.9	125.9
HP-212	20.3	72.7	83.1	93.4	103.8	114.1	124.5	134.8	145.2	165.9	186.6

■ Single Acting

Unit: liter (ℓ)

Model	Volume	2.5 bar	3 bar	3.5 bar	4 bar	4.5 bar	5 bar	5.6 bar	6 bar	7 bar	8 bar
HP-050s	0.1	0.4	0.4	0.5	0.5	0.6	0.6	0.7	0.7	0.8	0.9
HP-063s	0.2	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.6	1.8
HP-066s	0.2	0.9	1.0	1.2	1.3	1.4	1.5	1.7	1.8	2.0	2.3
HP-075s	0.3	1.1	1.2	1.4	1.5	1.7	1.8	2.0	2.1	2.5	2.8
HP-088s	0.5	1.8	2.0	2.3	2.6	2.8	3.1	3.3	3.6	4.1	4.6
HP-100s	0.7	2.5	2.9	3.2	3.6	3.9	4.3	4.6	5.0	5.7	6.4
HP-115s	1.2	4.3	4.9	5.5	6.1	6.7	7.3	8.0	8.6	9.8	11.0
HP-125s	1.5	5.4	6.1	6.9	7.7	8.4	9.1	10.0	10.7	12.3	13.8
HP-145s	2.4	8.6	9.8	11.0	12.3	13.5	14.8	15.9	17.2	19.6	22.1
HP-160s	3.1	11.1	12.7	14.3	15.8	17.4	18.9	20.6	22.2	25.3	28.5
HP-180s	4.3	15.4	17.6	19.8	22.0	24.2	26.4	28.6	30.8	35.1	39.5
HP-200s	5.9	21.1	24.1	27.2	30.2	33.2	36.2	39.2	42.2	48.2	54.2
HP-210s	7.8	27.9	31.9	35.9	39.9	43.8	47.8	51.8	55.8	63.7	71.7
HP-211s	5.1	18.3	20.9	23.5	26.1	28.7	31.3	33.9	36.5	41.7	46.9
HP-212s	9.6	34.4	39.3	44.2	49.1	54.0	58.9	63.8	68.7	78.4	88.2

Weight

Unit: kg

Model	HP-035	HP-050	HP-063	HP-066	HP-075	HP-088	HP-100	HP-115
Weight	0.54	1.16	1.68	2.4	3	4.3	6	9
Spring (1 ea)	NA	0.009	0.017	0.021	0.033	0.056	0.078	0.121

Model	HP-125	HP-145	HP-160	HP-180	HP-200	HP-210	HP-211	HP-212
Weight	11.3	14.1	22	26.5	38.4	46	46	71
Spring (1 ea)	0.165	0.202	0.359	0.521	0.752	0.882	14.1	28.2

Declutchable Gear Override - HGO-Series

■ Features

The HGO-series is designed and developed for small size valve automation to provide manual override capabilities in the event of an air supply failure. It mounts between a pneumatic actuator and a ball, butterfly, plug, damper valve.


Small, light, compact and high torque output design

Mounting base standard to ISO 5211


Solid & tight sealing with o-ring system giving weatherproof (IP67)

Self-lubricated worm shaft guide provides high reliability & stability

Block and bleed valve to exhaust air





■ Dimension



Model		A	B	C	D	E	F	G	H/J	Weight (Kg)	Max. Torque	Applicable actuators
HGO-010A	mm	81	159	240	158	112	104	14	F05, F07	3.2	12 kgf.m	HP-035~075
	inch	3.19	6.26	9.45	6.22	4.4	4.09	0.56			1040 lb.in	
HGO-010C	mm	81	159	240	158	112	104	14	F05, F07	5.1	12 kgf.m	HP-035~075
	inch	3.19	6.26	9.45	6.22	4.4	4.09	0.56			1040 lb.in	
HGO-050C	mm	104	212	316	229	469	148	22	F10, F12	16.1	50 kgf.m	HP-088~125
	inch	4.1	8.35	12.44	9.01	6.65	5.82	0.87			4340 lb.in	
HGO-080C	mm	104	220	324	261	204	154	27	F10, F12	17.1	80 kgf.m	HP-125~160
	inch	4.1	8.67	12.76	10.28	8.03	6.06	1.06			6943 lb.in	
HGO-150C	mm	128	274	402	346	300	190	36	F10, F14	42.8	150 kgf.m	HP-160~200
	inch	5.03	10.79	15.83	13.62	11.81	6.3	1.42			13019 lb.in	

※The last letter of the model name: A means Aluminum housing, C means Cast iron.

Dimension - Pinion Shaft Star Adapter



Unit: mm

Model	A	B	C	D	E
HP-050	9	11	12.5	15	13.5
HP-063	9	14	12.5	19.1	17.5
HP-066	11	14	14	19.1	20
HP-075	11	17	15	23.1	21.5
HP-088	14	17	19	23.1	21.5
HP-100	14	17	19	23.1	21.5
HP-115	14	22	19	29.6	31.5
HP-125	17	22	23	29.6	31.5
HP-145	17	27	23	36	35.5
HP-160	22	27	30	36	35.5
HP-180	27	36	37	48	39
HP-200	27	36	37	48	39
HP-210	27	36	37	48	43



Ordering Code

Double Acting Actuator

HP 050 - DA

Double Acting Configuration

Model / Cylinder Diameter

035 / 050 / 063 / 066 / 075 / 085 / 100 / 115 /
 125 / 145 / 160 / 180 / 200 / 210 / 211 / 212

Double Acting Actuator

HP 075 - S08 - C

Fail Position

C : Closed
 O : Open

Number of spring

S05 / S06 / S07 / S08 / S09 / S10 / S11 / S12

Model / Cylinder Diameter

035 / 050 / 063 / 066 / 075 / 085 / 100 / 115 /
 125 / 145 / 160 / 180 / 200 / 210 / 211 / 212



www.hkcon.co.kr

Headquarter / Factory

Add. Seonggok-dong, 155 Byeolmang-ro, Danwon-gu, Ansan-si, Gyeonggi-do, Korea (15417 or 425-836)

Tel. +82-31-488-8266

Fax. +82-31-488-8269 / 8696

E-mail. hkcon@hkcon.co.kr

Seoul office (Domestic sales)

Add. 1009ho, 278 beotkkot-ro, Geumcheon-gu, Seoul, Korea (08511)

Tel. +82-2-2138-8266

Fax. +82-2-2138-8269

E-mail. hk8266@hkcon.co.kr

Published product features and data do not express warranty and may be subject to change without prior notice.

Valve automation leader HKC